

Technical data

TROLDTEKT® DESIGN

Troldtekt acoustic panels are made of wood and cement. The product consists of wood (spruce), which is shredded into wood wool and mixed with cement. Customers can choose whether they want their Troldtekt acoustic panels to be FSC (FSC®C115450) or PEFC-certified. Both certifications guarantee

that the wood comes from responsible forestry operations.

Troldtekt design panels are surface-treated. Due to the nature of the material, colour variations will occur in natural wood and natural grey panels. These colour variations

are most evident in the natural grey panels, where the colour of the Troldtekt panels derives solely from the cement. Factors affecting colour variations include the water/cement ratio, the water content of the wood, the drying rate, steam curing and curing humidity.

PRODUCT STANDARDS, LABELLING AND CERTIFICATION

CE marking

Within the EU, all building materials are legally required to be CE-marked. The CE mark indicates that the building material can be legally sold and that it complies with the product standard to which the mark refers. Troldtekt products are CE-marked, and in addition to the marking we state:

Name of producer:

Troldtekt A/S

Certifications

0615-CPD-222958G

0615-CPD-804474G

Product standard number:


EN 13168 and EN 13964

Declaration:

See product data on page 2

Other approvals

Cradle to Cradle: Troldtekt is Cradle to Cradle-certified at Gold level. Troldtekt acoustic panels are documented as being free of harmful substances and can therefore safely be returned to the biological cycle. Additionally, waste from the production of Troldtekt acoustic panels is returned to the technical cycle and used as a resource in new cement at Aalborg Portland.



Indoor climate labelling: Troldtekt is indoor climate-labelled in the best degassing and particle release categories.



M1 classification: Troldtekt is M1-classified by the Finnish Building Information Foundation RTS sr. This is the best category, and means that the panels have an extremely low emissions level for volatile organic compounds (VOC).



Blue Angel: Troldtekt is eco-labelled under the German Blue Angel eco-labelling scheme, which guarantees that the product has a low impact on the environment and the climate and meets high standards for health protection.



PEFC and FSC: Troldtekt is PEFC™ and FSC®-certified (FSC C115450), which means that all our products are manufactured using wood from responsible forestry operations. Customers can choose whether they want their Troldtekt acoustic panels to be FSC or PEFC-certified.



Light reflection: Light reflection for different types of Troldtekt panels (measured by DELTA/Force Technology):

Troldtekt white 101	70.8 %
Troldtekt natural wood	55.2%
Troldtekt natural grey	26.3%

OPERATION AND MAINTENANCE

Troldtekt acoustic panels usually require no subsequent care. However, we recommend regular cleaning along with other surfaces – and otherwise as required. The panels are

easy to clean using a vacuum cleaner with a brush nozzle. If vacuum-cleaning is not sufficient, the panels can be wiped with a slightly damp cloth. If you want to paint

the Troldtekt ceiling, use a long-haired paint roller or a hand sprayer. Water-based paint does not reduce the sound-absorbing properties of the panels.

REUTILISATION

The entire range of Troldtekt's cement-bonded wood wool panels is Cradle to Cradle-certified at Gold level. Consequently, we have complete documentation of the substances in the products, and documentation that the products can be composted and safely retur-

ned to the biological cycle as a soil conditioner. The cement in Troldtekt panels has a high lime content, which helps to neutralise the acids produced during composting. The wood in the Troldtekt panels is organic material, and helps to prevent the compost

from compacting, thereby enhancing oxygenation during the composting process. In this way, carbon and nutrients are recirculated in the biological cycle.

TOLERANCES

Troldtekt consists of the natural material wood, and cement extracted from Danish mineral resources. The mix of natural materials – wood wool and cement – inevitably results in slight variations in the panels. Panel

dimensions and weights remain inside the tolerance indicated at 23+/-2°C and 50+/-5% relative humidity. However, inappropriate storage and lack of acclimatisation can affect the dimensions and weight of the

panels. It is therefore important that you observe the installation, storage and acclimatisation instructions carefully.

PRODUCT DATA

The table below indicates the tolerances declared by us in accordance with EN 13168, which is the standard for cement-bonded wood wool and double-layer panels with cement-bonded wood wool, and EN 13964, the standard for suspended ceilings.

Properties:

DIMENSIONS (mm)

Produktname	T	B	L
V-Line	25	600	1200
Line	35	600	1200
Line Design	35	604	1194
Tilt Line	35	600	1200
Curves	35	600	1200
Dots	35	600	1200
Tiles	35	600	600
Puzzle	35	600	600
Rhombe Mini	35	600	693
Rhombe Hatch Mini	35	600	693
Rhombe	35	600	1039
Rhombe Hatch	35	600	1039
Contrast	35	600	1200

TOLERANZEN

Length (mm)	≥ 1250 : ±2.0
	≤ 1250 : ±1.0
Width (mm)	±1.0
Thickness (mm)	Length ≥ 1250 : ±2.0
	Length ≤ 1250 : ±1.0
Weight %	±10
Perpendicularity (mm/m)	± ≤ 2
Planeness (mm)	± ≤ 3

FIRE

Reaction to fire In accordance with EN 13501-1	B-s1,d0	A2-s1,d0	D-s2,d2
Fire protection ability In accordance with EN 13501-2	K ₁ 10/K ₂ 10		K ₁ 10/K ₂ 10
Cladding class	K ₁ 10/B-s1,d0 (Class 1 cladding)	K ₁ 10/D-s2,d2 (Class 2 cladding)	

WEIGHT (ultrafine structure)

Product name

V-line	10.9 kg/m ²	12.7 kg/m ²
Line	14.7 kg/m ²	15.7 kg/m ²
Line design	14.7 kg/m ²	15.7 kg/m ²
Other Line design	15.1 kg/m ²	16.1 kg/m ²
Tilt line	15.8 kg/m ²	16.8 kg/m ²
Curves	15.7 kg/m ²	16.8 kg/m ²
Dots	15.8 kg/m ²	16.9 kg/m ²
Tiles 4 + 4	15.1 kg/m ²	16.1 kg/m ²
Other Tiles	15.7 kg/m ²	16.8 kg/m ²
Puzzle	16.1 kg/m ²	17.2 kg/m ²
Rhombe mini	16.4 kg/m ²	17.5 kg/m ²
Rhombe hatch mini	16.3 kg/m ²	17.4 kg/m ²
Rhombe	16.3 kg/m ²	17.4 kg/m ²
Rhombe hatch	15.6 kg/m ²	16.7 kg/m ²
Contrast 9 tracks incl. strips	24.0 kg/m ²	

SUBSTANCES In accordance with EN

Chloride	≤ 0.06
Formaldehyde	E1*

SUSPENSION

Declaration in accordance with	EN 13168
	EN 13964

* No measurable formaldehyde emission